

# **AIRCRAFT ARCHWAY ARCHITECTURE**

## **TECHNICAL FIELD**

**[0001]** The present invention relates to architectural structures for aircraft and more particularly to improved structures, cabin furnishing, accessories and auxiliary equipment for aircraft.

## **BACKGROUND OF THE INVENTION**

**[0002]** The interior configuration and architecture of aircraft have become relatively standardized today. The arrangements of the passenger seats, bulkheads, lavatories, serving areas, and crew spaces have been developed for convenience and accommodation of both passengers and crew. The passenger compartments are typically divided into two or more sections with bulkheads and lavatories being positioned accordingly. Aisles and passageway spaces are left between sets of seats and at the access doors.

**[0003]** The support lines and conduits for the accessory and auxiliary systems, such as conditioned air, water, hydraulics and electrical systems, are typically positioned in the lower bay below the passenger compartment (cabin) or in the crown or space above the passenger cabin. For some of these accessory systems, such as conditioned air and electrical systems, the wires and lines are passed between the lower bay and crown, or between one of those areas and the passenger cabins through the sidewalls or support members adjacent the exterior of the aircraft.

**[0004]** The installation, repair, and modification of the accessory and auxiliary systems, as well as the cabin furnishings, is a considerable expense to aircraft owners and users. There is a need for improved interior systems and for more efficient design and use of cabin furnishings and associated systems.

**[0005]** Often, the design and installation of cabin furnishing and auxiliary systems result in modification to the system transport elements, such as electrical wiring, fluid lines, and environmental control system ducts, which result in an increased cost and lead time for delivery of the desired aircraft. The problem is amplified for those transport systems that pass between the crown



and lower bay of the aircraft since this may result in the loss of windows and sidewalls or longer than desired runs to fixed monuments at bulkheads.

**[0006]** There is a need in the aircraft industry for improved, more efficient, less complex, and less costly configurations for cabin furnishings and associated auxiliary systems in order to obviate the afore-mentioned problems.

### **SUMMARY OF THE INVENTION**

**[0007]** In accordance with the present invention, one or more arch-type members ("archways") are positioned in the cabin of the aircraft. The archways preferably are inverted generally "U-shaped" structures which extend along the inside surfaces of the passenger cabins and have hollow interiors for placement and passage of electrical wires, air conditioning ducts, water lines and the like. The archways are placed at stable locations within the cabin, such as at fixed door locations, so that they will reduce potential impact on seat configurations. The archways provide a path or raceway for the system transport elements particularly between the crown and lower bays of the aircraft.

**[0008]** The archways also can be positioned at architectural points of interest in the aircraft to help define and establish cabin proportions and also provide logical locations for passage of auxiliary system components. Placement of the archways at door locations provides a passage to run systems at each doorway without interfering with structural intercoastals located between framed bays at the door locations. The archways allow penetration through the floor of the cabin which can be standardized, reducing the variation in floor panel design. In addition, the archways can serve as receptacles for lavatory and gallery monuments, further reducing the complexity associated with integrating those elements into the interior of the aircraft. The archways further can eliminate the need for design close-out seals for outboard monuments.

**[0009]** The present invention simplifies the installation complexity and eliminates the installation variability associated with installing and running transport elements between the crown and lower bays of the aircraft.



## **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0010]** FIGURE 1 illustrates an aircraft in which the present invention can be utilized.

**[0011]** FIGURE 2 is a cross-section through the aircraft as shown in Figure 1 and depicting use of the present invention.

**[0012]** FIGURE 3 is a perspective view of an aircraft cabin interior, illustrating the use of the present invention.

**[0013]** FIGURE 4 is a perspective view illustrating the use of a plurality of archways in an aircraft in accordance with the present invention.

**[0014]** FIGURE 5 depicts the use of a pair of inventive archways at an exterior door to the passenger compartment.

**[0015]** FIGURE 6 is a cross-sectional view of the archways as shown in Figure 2.

**[0016]** FIGURE 7 is a cross-section of an alternate embodiment of an archway in accordance with the present invention.

**[0017]** FIGURE 8 is a cross-section of still another alternate embodiment of an archway in accordance with the present invention.

**[0018]** FIGURE 9 illustrates use of the present invention for lavatories and other accessory systems.

**[0019]** FIGURE 10 depicts a cross-section of still another alternate embodiment of an archway in accordance with the present invention.

## **DESCRIPTION OF PREFERRED EMBODIMENTS**

**[0020]** Efficient interior configuration and modification of airplanes and other aircraft is of value to airline companies and customers by reducing the costs associated with designing and installing cabin furnishings and auxiliary and support systems. Often, these activities will result in modifications to system transport elements, such as electrical wiring, water lines, or environment control system ducts resulting in increased costs and lead time for delivery of the desired aircraft. This problem is amplified for those transport elements that must run or be passed between the airplane crown and the lower lobe or bay,



since current design practices result in loss of windows in the sidewalls, or longer than desired runs to fixed monuments at the fore or aft bulkheads.

**[0021]** The complexity and costs associated with providing for system runs between the crown and lower bays of airplanes and other aircraft has a significant impact on interior architecture, interior flexibility, body structure at doorways and manufacturing installation time. The present invention simplifies the installation complexity and eliminates the installation variability associated with running transport elements between the crown and lower bay areas.

**[0022]** In particular, the present invention uses architectural arches or archways at one or more locations along the length of the aircraft. The archways provide raceways or passageways for system transport elements, particularly for those which need to be passed from the crown to the lower bay of the aircraft. The archways also can be placed at stable locations within the fuselage or cabin of the aircraft, such as at fixed door locations which reduce the potential impact on seat configuration and provide improved cabin configurations.

**[0023]** Archways located on either side of a doorway will enable a number of different functions, such as architectural delineation of cabin volumes that are properly proportioned, and enclosure of system transport elements, including, but not limited to, electrical power and signal, water and conditioned air. The architectural archways also can incorporate a stable floor coupling in order to pass system transporting elements through the floor while meeting existing requirements for floor penetrations.

**[0024]** The inventive archways further will provide accommodation for items, including, but not limited to, system control panels, lavatories, emergency equipment and flight attendant seats. When properly sized and configured, the archways will have the ability to provide for retractable features or otherwise hide these elements within the archway when not in use.

**[0025]** With the present invention, an altered method for interior cabin lighting via recessed task lighting can result, particularly through the use of luminescent cover panels or wash lighting from within the archways. The present invention will also provide a way to more efficiently create and control



air temperature zones within the cabin by using an archway located air curtain to prevent air draft from moving fore and aft between cabins.

**[0026]** The present invention further can reduce the impact of external temperature extremes on cabin interior temperatures while in the boarding or deplaning processes.

**[0027]** With the present invention, various stations or zones within the cabin can be designated where passengers can experience a local enhanced air environment contained within a station or zone. This could include local humidification, increased air mixing, or ionized/purified air.

**[0028]** Finally, the present invention can provide a more integrated look for outboard lavatories or gallery monuments by designing the archways to accept the modules without the use of closeout seals or foams. In this regard, system connections servicing these monuments can be readily accessible.

**[0029]** The use of archways located at doorways can serve as a system plenum to connect the systems that run between the crown of the airplane, the lower lobe or bay, and the main passenger cabin. The archways can assist in defining and establishing cabin proportions and also provide logical locations for system runs associated with water, power, and conditioned air. The placement at door locations provides a way to run systems at each doorway without having to interfere with the structural intercostals located between frame bays typically positioned at door locations.

**[0030]** With the present invention, the penetration through the floor can be standardized which will reduce the variation in floor panel designs.

**[0031]** If the archways are used for lavatory and galley monuments, this can reduce the complexity associated with integrating these elements into the interior, as well as eliminating the need for designed closeout seals for outboard monuments.

**[0032]** Figure 1 is a perspective view of an airplane or aircraft in which the present invention can be utilized. The airplane is referred to generally by the reference numeral 20.

**[0033]** Figure 2 is a representative cross-section 2-2 taken at a location along the length of the fuselage or cabin of the airplane 20. As indicated, the



aircraft includes a main passenger cabin 24, an upper crown area 26 and a lower lobe or bay 28, all positioned with an outer skin or exterior 30 of the airplane. The lower bay 28 typically is utilized for transporting luggage and other material. The passenger cabin or compartment 24 includes a number of passenger seats 32 which are positioned on a floor member 34 that extends across the width of the airplane 20. Also, as conventional in airplanes today, a number of luggage or storage bins 36A, 36B, and 36C are provided on the upper portion of the passenger cabin 24.

**[0034]** An architectural arch or archway 40 is shown in its representative position within the airplane 20. The archway has a semi-circular or curved configuration as shown and is attached to the floor member 34 at its two lower ends 40A and 40B. The archway can be attached to the floor member in any conventional manner. The archway 40 preferably has a V-shaped cross-section as shown in Figure 6. Although a V-shaped cross-section is preferred, it is also possible within the scope of the present invention for the archway 40 to have other cross-sectional sizes and shapes. For example, the archway 140, as shown in Figure 8, has an expanded U-shaped cross-sectional configuration and shape, while the archway 240 as shown in Figure 10 has a semi-circular or curved cross-sectional shape and configuration.

**[0035]** As shown in Figure 2, an aircraft, such as airplane 20, has a number of control, auxiliary and support systems which have wires and conduits which need to be passed or run along the length of the aircraft and to be utilized at various positions along the length of the aircraft. These lines and conduits also need to be passed at some locations between the crown and lower bay areas of the aircraft. The conduits for these systems are shown in Figure 2 and are represented generally by reference numerals 42, 44, 46, 48, and 50. The conduits and systems mentioned and shown are only representative of the known and conventional systems used in aircraft today, such as electrical wiring, control wiring, water lines, air ducts, environment control system ducts, etc.

**[0036]** With the configuration shown, the system wires and conduits 42, 44, and 46 are positioned in the upper portion or crown 26 of the fuselage of the



aircraft. In addition, other systems and conduits, such as 48 and 50 shown in Figure 2, are positioned in the lower lobe or bay of the aircraft. In order to utilize these systems, the archways 40 of the present invention allow or act as passageways or chaseways for the electrical lines and other conduits, such as 42A, 44A, and 46A, 48A and 50A. As shown in the cross-sectional view in Figure 6, the conduits are positioned in the interior open space of the archway 40. Some of these same conduits and wires are also shown in Figures 8 and 10.

**[0037]** In accordance with the present invention, it is also possible to have one or more of the conduits or ducts be molded or provided as part of the archway itself. This is shown in Figure 7, where archway 40' has a cross member 54 which forms an enclosed plenum or chamber 56. It is also to be understood, of course, that any number of interior conduits and plenums can be provided in the archways in accordance with the present invention and thus the invention is not limited to a structure having at least one plenum or any number thereof.

**[0038]** It is to be understood that the various cross-sectional sizes and shapes of the archways 40, 140, and 240 are only illustrative of the various cross-sectional sizes and shapes of archways that can be utilized in accordance with the present invention. Thus, the present invention is not limited to any particular size or shape of cross-section.

**[0039]** It is also possible to provide more than one integral or "built-in" conduit or passageway in the archway. Also, the integral conduits or passageways do not have to extend the full length of the archway, but can be positioned only in one or more portions thereof, such as in the portions which are positioned along the inner sides of the aircraft fuselage. It is further possible to provide one or more archways for the aircraft which are not hollow at all, or are only hollow along portions thereof.

**[0040]** In accordance with one embodiment of the present invention, pairs of arches or archways 40 can be positioned at various locations along the length of the aircraft or airplane. This is shown in Figures 3-5. First, as shown in Figure 4, two sets A, B of pairs of archways 40 are shown located at two positions in the fuselage of airplane 120. An interior view of the fuselage 60 in



the direction of the length of the fuselage is shown in Figure 3. The archways 40 are used to separate the fuselage into various cabins C1, C2, and C3 along the length of the airplane.

**[0041]** A side elevational view illustrating one of the pairs of archways 40A is shown in Figure 5. The pair of archways 40A are also used to frame a door member 62. In this regard, as shown in Figures 3 and 5, various partitions 64 and 66 can be positioned in or adjacent to the archways 40, 40A in order to assist in separating the interior cabins, such as C1, C2 and C3, from one another.

**[0042]** It is to be understood in accordance with the present invention, that any number of archways can be provided along the length of the fuselage of an airplane or aircraft. It is also understood that any number of pairs or sets of archways can be provided at various locations along the length of the aircraft.

**[0043]** As shown in Figure 9, archways in accordance with the present invention can also be used to house or accommodate various accessories or auxiliary systems which are common in passenger airplanes today. In this regard, archways 80 and 82 are used to frame or flank a door member 62' at a location along the length of the airplane. Archway 80 is sufficiently wide to incorporate a lavatory 90, while archway 82 has a size sufficient to incorporate a jump seat 92 for one of the flight attendants. Also, as shown in Figure 9, an archway can be modified to incorporate various other items and systems, such as telephone 94 and electronic controls 96 for other systems on the airplane.

**[0044]** While the invention has been described in connection with one or more embodiments, it is to be understood that the specific mechanisms, processes and procedures which have been described are merely illustrative of the principles of the invention, numerous modifications may be made to the methods and apparatus described without departing from the spirit and scope of the invention as defined by the appended claims.